

Output Ratings		
Genset Model	Prime ¹	Standby ²
380-415V, 50Hz	13kVA / 10.4kW	15kVA / 12kW
480V, 60Hz	TBA	TBA
Ratings are given at 0,8 power factor		

Dimension & Weight				
Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
1550/1960	900/900	1000/1380	504/698	510/705

Dry: With Lube Oil Wet: With Lube Oil & Coolant

Without canopy/ with canopy

Engine Technical Data	
Engine Model :	Perkins 403A-15G1
Number of Cylinders:	3 / Inline
Cycle :	4 Stroke
Bore / Stroke [mm] :	84.0 / 90.0
Induction :	Naturally Aspirated
Cooling Method :	Water
Governor Type :	Mechanical
Compression Ratio :	22.5:1
Displacement [lt] :	1.5
Electrical Sys. Voltage	12 / Negative
Battery Charger Amps.	15

Lubrication System	
Total Oil Capacity [lt] :	6.0
Oil Type :	API CH4 15W-40
Oil Cooling Method :	-

Fuel System	
Fuel Filter Type :	Replaceable Element
Recommended Fuel :	Class A2 Diesel
Fuel Consumption [lt] :	
	110% 100% 75% 50%
Prime	Load Load Load Load
50Hz	4.1 3.7 2.8 2
60Hz	

	110% 100% 75% 50%
Standby	Load Load Load Load
50Hz	
60Hz	

(Based on diesel fuel with a spec. gravity of 0,84 and complied with BS2869, Class A2)

Alternator Data	
Manufacturer :	Linz Electric
Model :	E1X13ME/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	85.5%
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Apparent power [kVA]:	14.2
Radiant Heat [Kw]:	
	50Hz 1.4
	60Hz TBA

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.

Cooling System	50Hz	60Hz
Cooling System Capacity [lt] :	5.3	5.3
Heat rejected to Water & Lube Oil [kW]:		
Prime	11.6	13.6
Standby	12.9	15.2
Heat Radiation to Room [kW] :		
Prime	5.0	5.9
Standby	5.5	6.6
Radiator Fan Load [kW] :	0.2	0.3
Radiator Cooling Air Flow [m³/min] :	28.8	37.2
External Restrictions to :		
Cooling Airflow [Pa] :	125	125

Exhaust System	50Hz	60Hz
Max. Allowable Back Pressure [kPa] :		
	10.2	10.2
Exhaust Gas Flow [m³/min] :		
Prime	2.7	3.1
Standby	2.9	3.4
Exhaust Gas Temp. [°C] :		
Prime	445	455
Standby	490	505

Performance	50Hz	60Hz
Engine Speed [rpm] :	1500	1800
Gross Engine Power [kW] :		
Prime	12.2	14.7
Standby	13.5	16.2

Air Systems	50Hz	60Hz
Air Filter Type :	Replaceable Element	
Combustion Air Flow [m³/min] :		
Prime	1.1	1.2
Standby	1.1	1.2
Max. Combustion Air Intake		
Restriction [kPa] :	3.0	3.0

Available Options	
Diamond offers a range of optional features to tailor our gensets to meet your power requirements.	
Options:	
* A wide range of Sound Attenuated Enclosures	
* A variety of generating set control and synchronising panels	
* Additional alarms and shutdowns	
* A selection of exhaust silencer noise levels	
For further information on all of the standard and optional features for this product, please contact DIAMOND or visit www.diamondcable.com.tr	