

Genset Model	Prime ¹	Standby ²
380-415V, 50Hz	1710kVA / 1368kW	1875kVA / 1500kW
480V, 60Hz	-	-

Ratings are given at 0,8 power factor

Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
5060/9145	2260/2468	2420/3950	10600/17800	10707/19807

Wet: With Lube Oil & Coolant

Lubrication System	
Engine Model :	Perkins 4012-46TAG3A
Number of Cylinders:	12 / V
Cycle :	4 Stroke
Bore / Stroke [mm] :	160.0 / 190.0
Induction :	Turbocharged CAC
Cooling Method :	Water
Governor Type :	Electronic
Compression Ratio :	13.6:1
Displacement [lt] :	45.8
Electrical Sys. Voltage	24 / Negative
Battery Charger Amps.	40

Total Oil Capacity [lt] :	177.0
Oil Type :	API CH4 15W-40
Oil Cooling Method :	Water

Fuel Filter Type :	Replaceable Element			
Recommended Fuel :	Class A2 Diesel			
Fuel Consumption [lt] :				
	110%	100%	75%	50%
Prime	Load	Load	Load	Load
50Hz	405	370	275	187
60Hz	-	-	-	-

	110%	100%	75%	50%
Standby	Load	Load	Load	Load
50Hz		405	305	206
60Hz		-	-	-

Manufacturer :	Stamford
Model :	PI 734E
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	95.8%
Voltage Regulation (Steady State) :	1%
Total Harmonic Content:	3.0%
Appearent power [kVA]:	2035
Radiant Heat [Kw]:	

Cooling System Capacity [lt] :	207.0	-
Heat rejected to Water & Lube Oil [kW]:		
Prime	510.0	-
Standby	625.0	-
Heat Radiation to Room [kW] :		
Prime	110.0	-
Standby	123.0	-
Radiator Fan Load [kW] :	-	-
Radiator Cooling Air Flow [m ³ /min] :	1920.0	-
External Restrictions to :		
Cooling Airflow [Pa] :	250	-

Max. Allowable Back Pressure [kPa] :			
		5.0	-
Exhaust Gas Flow [m ³ /min] :			
	Prime	-	-
	Standby	350.0	-
Exhaust Gas Temp. [°C] :			
	Prime	-	-
	Standby	480	-

Engine Speed [rpm] :	1500	-
Gross Engine Power [kW] :		
Prime	1500	-
Standby	1643	-

Air Filter Type :		Replaceable Element	
Combustion Air Flow [m ³ /min] :			
Prime	125.0	-	
Standby	135.0	-	

Restriction [kPa]:	4.0	-
--------------------	-----	---

features for this product, please contact DIAMOND or visit www.diamondcable.com.tr

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standard reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.