

Output Ratings		
Genset Model	Prime ¹	Standby ²
380-415V, 50Hz	250kVA / 200kW	275kVA / 220kW
480V, 60Hz	TBA	TBA

Ratings are given at 0,8 power factor

Dimension & Weight				
Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
2750/3640	1250/1250	1680/2100	1809/2460	-

Dry: With Lube Oil

Wet: With Lube Oil & Coolant

Without canopy/ with canopy

Engine Technical Data	
Engine Model :	Volvo TAD734GE
Number of Cylinders:	6 / Inline
Cycle :	4 Stroke
Bore / Stroke [mm] :	108 / 130
Induction :	Turbocharged CAC
Cooling Method :	Water
Governor Type :	Electronic
Compression Ratio :	18:01
Displacement [lt] :	7.15
Electrical Sys. Voltage	24V/Negative
Battery Charger Amps.	100A

Lubrication System	
Total Oil Capacity [lt] :	29
Oil Type :	API: CG-4, CH-4 15W-40
Oil Cooling Method :	Water

Fuel System	
Fuel Filter Type :	Replaceable Element
Recommended Fuel :	ASTM-D975-No1 and 2-D
Fuel Consumption [lt] :	
	110% 100% 75% 50%
Prime	Load Load Load Load
50Hz	60,7 54,6 43,6 31,2
60Hz	- - - -

	110% 100% 75% 50%
Standby	Load Load Load Load
50Hz	60,7 45,1 34,3
60Hz	- - -

(Based on diesel fuel with a spec. gravity of 0,84 and complied with BS2869, Class A2)

Alternator Data	
Manufacturer :	Linz Electric
Model :	PRO28S D/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	92.7%
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Apparent power [kVA]:	280

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Cooling System	50Hz	60Hz
Cooling System Capacity [lt] :	24	-
Heat rejected to Water & Lube Oil [kW]:		
Prime	117	-
Standby	128	-
Heat Radiation to Room [kW] :		
Prime	24	-
Standby	26	-
Radiator Fan Load [kW] :	11.6	-
Radiator Cooling Air Flow [m ³ /min] :	314	-
External Restrictions to :		
Cooling Airflow [Pa] :	350	-

Exhaust System	50Hz	60Hz
Max. Allowable Back Pressure [kPa] :		
	10.0	-
Exhaust Gas Flow [m ³ /min] :		
Prime	-	-
Standby	33.4	-
Exhaust Gas Temp. [°C] :		
Prime	495	-
Standby	550	-

Performance	50Hz	60Hz
Engine Speed [rpm] :	1500	-
Gross Engine Power [kW] :		
Prime	225	-
Standby	250	-

Air Systems	50Hz	60Hz
Air Filter Type :	Replaceable Element	
Combustion Air Flow [m ³ /min] :		
Prime	16.1	-
Standby	16.3	-

Max. Combustion Air Intake

Restriction [kPa] : - -

Available Options	
Diamond offers a range of optional features to tailor our gensets to meet your power requirements.	
Options:	
* A wide range of Sound Attenuated Enclosures	
* A variety of generating set control and synchronising panels	
* Additional alarms and shutdowns	
* A selection of exhaust silencer noise levels	
For further information on all of the standard and optional features for this product, please contact DIAMOND or visit www.diamondcable.com.tr	