

Output Ratings

Genset Model	Prime ¹	Standby ²
380-415V, 50Hz	640kVA / 512kW	710kVA / 568kW
480V, 60Hz	TBA	TBA

Ratings are given at 0,8 power factor

Dimension & Weight

Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
3650/4670	1640/1640	2110/2500	4405/5325	-

Dry: With Lube Oil

Wet: With Lube Oil & Coolant

Without canopy/ with canopy

Engine Technical Data

Engine Model :	Volvo TWD1643GE
Number of Cylinders:	6 / Inline
Cycle :	4 Stroke
Bore / Stroke [mm] :	144 / 165
Induction :	Turbocharged CAC
Cooling Method :	Water
Governor Type :	Electronic
Compression Ratio :	16.5:1
Displacement [lt] :	16.12
Electrical Sys. Voltage	24V/Negative
Battery Charger Amps.	80A

Lubrication System

Total Oil Capacity [lt] :	48
Oil Type :	API: CG-4, CH-4 15W-40
Oil Cooling Method :	Water

Fuel System

Fuel Filter Type :	Replaceable Element
Recommended Fuel :	ASTM-D975-No1 and 2-D

Fuel Consumption [lt] :

	110%	100%	75%	50%
Prime	Load	Load	Load	Load
50Hz	145,2	131,0	96,8	64,5
60Hz	-	-	-	-

	110%	100%	75%	50%
Standby	Load	Load	Load	Load
50Hz		145,2	108,1	71,0
60Hz		-	-	-

(Based on diesel fuel with a spec. gravity of 0.84 and complied with BS2869, Class A2)

Alternator Data

Manufacturer :	Linz Electric
Model :	PRO35MF/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	6
Protection Class :	IP23
Efficiency:	94.7%
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Appearent power [kVA]:	735
Radiant Heat [Kw]:	
	50Hz
	25.74
	60Hz
	TBA

Cooling System

Cooling System Capacity [lt] :	95.0	-
Heat rejected to Water & Lube Oil [kW]:		
Prime	208	-
Standby	226	-
Heat Radiation to Room [kW] :		
Prime	23	-
Standby	33	-
Radiator Fan Load [kW] :	17	-
Radiator Cooling Air Flow [m ³ /min] :	967	-
External Restrictions to :		
Cooling Airflow [Pa] :	200	-

Exhaust System

Max. Allowable Back Pressure [kPa] :			
		10	-
Exhaust Gas Flow [m³/min] :			
	Prime	101.6	-
	Standby	111.8	-
Exhaust Gas Temp. [°C] :			
	Prime	450	-
	Standby	463	-

Performance

Engine Speed [rpm] :	1500	-
Gross Engine Power [kW] :		
Prime	553	-
Standby	613	-

Air Systems

Air Filter Type :		Replaceable Element	
Combustion Air Flow [m³/min] :			
Prime	43.65	-	
Standby	46.96	-	

Max. Combustion Air Intake

Restriction [kPa]: 5.0 -

Available Options

Diamond offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

- * A wide range of Sound Attenuated Enclosures
- * A variety of generating set control and synchronising panels
- * Additional alarms and shutdowns
- * A selection of exhaust silencer noise levels

For further information on all of the standard and optional

features for this product, please contact DIAMOND or

visit www.diamondcable.com.tr

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)