

Output Ratings		
Genset Model	Prime ¹	Standby ²
10000V, 50Hz	2015kVA / 1612kW	2276kVA / 1820kW

Ratings are given at 0,8 power factor

Dimension & Weight				
Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
11000	2500	3000	TBA	

Dry: With Lube Oil Wet: With Lube Oil & Coolant

Without canopy/ with canopy

Lubrication System	
Engine Model :	Mitsubishi S16R-PTAW2
Number of Cylinders:	16 / V
Cycle :	4 Stroke
Bore / Stroke [mm] :	170.0 / 180.0
Induction :	Turbocharged - Air Cooler
Cooling Method :	Water
Governor Type :	Elektronic
Compression Ratio :	13.5:1
Displacement [lt] :	65.37
Electrical Sys. Voltage	24 / Negative
Battery Charger Amps.	30

Lubrication System	
Total Oil Capacity [lt] :	230
Oil Type :	API CD 15W-40
Oil Cooling Method :	Ceket suyu

Fuel System				
Fuel Filter Type :	Replaceable Element			
Recommended Fuel :	Class A2 Diesel			
Fuel Consumption [lt] :				
	110%	100%	75%	50%
Prime	Load	Load	Load	Load
50Hz	432	395	310	215

(Based on diesel fuel with a spec. gravity of 0,84 and complied with BS2869, Class A2)

Alternator Data	
Manufacturer :	STAMFORD
Model :	PI 734F
No. of Bearings :	Single
Insulation Class:	F
Winding Pitch :	2/3
Number of Wire :	6
Protection Class :	IP23
Efficiency:	96%
Voltage Regulation (Steady State) :	1%
Total Harmonic Content:	3.0%
Apparent power [kVA]:	2080

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Cooling System		50Hz
Cooling System Capacity [lt] :		670
Heat rejected to Water & Lube Oil [kW]:		
	Prime	
	Standby	
Heat Radiation to Room [kW] :		
	Prime	
	Standby	
Radiator Fan Load [kW] :		
Radiator Cooling Air Flow [m ³ /min] :		
External Restrictions to :		
Cooling Airflow [Pa] :		

Exhaust System		50Hz
Max. Allowable Back Pressure [kPa] :	
Exhaust Gas Flow [m ³ /min] :		
	Prime
	Standby
Exhaust Gas Temp. [°C] :		
	Prime	...
	Standby

Performance		50Hz
Engine Speed [rpm] :		1500
Gross Engine Power [kW] :		
	Prime	1777
	Standby	1947

Air Systems		50Hz
Air Filter Type :		Değiştirilebilir Elemanlı
Combustion Air Flow [m ³ /min] :		
	Prime
	Standby

Max. Combustion Air Intake

Restriction [kPa] :

Available Options	
Diamond offers a range of optional features to tailor our gensets to meet your power requirements.	
Options:	
* A wide range of Sound Attenuated Enclosures	
* A variety of generating set control and synchronising panels	
* Additional alarms and shutdowns	
* A selection of exhaust silencer noise levels	
For further information on all of the standard and optional features for this product, please contact DIAMOND or visit www.diamondcable.com.tr	