

Output Ratings

Genset Model	Prime ¹	Standby ²
380-415V, 50Hz	480 kVA / 384 kW	528 kVA / 422 kW
480V, 60Hz	-	-

Ratings are given at 0,8 power factor

Dimension & Weight

Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
3850 / 5170	1450 / 1650	2400 / 2600		

Dry: With Lube Oil

Wet: With Lube Oil & Coolant

Without canopy/ with canopy

Engine Technical Data

Engine Model :	SDEC - SC 25G610D2
Number of Cylinders:	12 / V
Cycle :	4 Stroke
Bore / Stroke [mm] :	135 / 150
Induction :	Turbocharged - Intercooled
Cooling Method :	Water cooled
Governor Type :	Electronic
Compression Ratio :	16.0:1
Displacement [lt] :	25.8
Electrical Sys. Voltage	24 / Negative

Cooling System

50Hz

Cooling System Capacity [lt] :

115

Lubrication System

Total Oil Capacity [lt] :	65
---------------------------	----

Exhaust System

50Hz

Max. Allowable Back Pressure [kPa] :

6

Fuel System

Fuel Filter Type :		Replaceable Element		
Recommended Fuel :		Class A2 Diesel		
Fuel Consumption [lt] :				
	110%	100%	75%	50%
Prime	Load	Load	Load	Load
50Hz	112.7	100.4	75.8	53.6

Exhaust Gas Temp. [°C] :

650

Performance

50Hz

Engine Speed [rpm] :

1500

Gross Engine Power [kW] :

Prime

405

Standby

445

Fuel Tank Capacity (L):

Air Systems

50Hz

Air Filter Type :

Replaceable Element

(Based on diesel fuel with a spec. gravity of 0,84 and complied with B52869, Class A2)

Alternator Data

Manufacturer :	Linz Electric
Model :	PRO 35 SC/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	94.9%
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Apparent power [kVA]:	550

Available Options

Diamond offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

* A wide range of Sound Attenuated Enclosures

* A variety of generating set control and synchronising panels

* Additional alarms and shutdowns

* A selection of exhaust silencer noise levels

For further information on all of the standard and optional

features for this product, please contact DIAMOND or

visit www.diamondcable.com.tr

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.