

Output Ratings		
Genset Model	Prime ¹	Standby ²
380-415V, 50Hz	19 kVA / 15.2 kW	21 kVA / 16.8 kW
480V, 60Hz	-	-
Ratings are given at 0,8 power factor		

Dimension & Weight				
Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
1550 / 1960	900 / 900	1000 / 1380	565 / 795	
Dry: With Lube Oil		Wet: With Lube Oil & Coolant		
Without canopy/ with canopy				

Engine Technical Data	
Engine Model :	WEICHAİ - WP 2.1D18E2
Number of Cylinders:	4 / Inline
Cycle :	4 Stroke
Bore / Stroke [mm] :	85 / 92
Induction :	Natural
Cooling Method :	Water cooled
Governor Type :	Mechanic
Compression Ratio :	18.0:1
Displacement [lt] :	2.08
Electrical Sys. Voltage	12 / Negative

Cooling System	50Hz
Cooling System Capacity [lt] :	

Lubrication System	
Total Oil Capacity [lt] :	8

Exhaust System	50Hz
Max. Allowable Back Pressure [kPa] :	10

Fuel System				
Fuel Filter Type :	Replaceable Element			
Recommended Fuel :	Class A2 Diesel			
Fuel Consumption [lt] :				
	110%	100%	75%	50%
Prime	Load	Load	Load	Load
50Hz	5	4.6	3.6	2.5

Exhaust Gas Temp. [°C] :	
	Standby
	500
Performance	
Engine Speed [rpm] :	1500
Gross Engine Power [kW] :	
	Prime
	17.5
	Standby
	19.3

Fuel Tank Capacity (L):	56
---------------------------	----

Air Systems	50Hz
Air Filter Type :	Replaceable Element

(Based on diesel fuel with a spec. gravity of 0,84 and complied with B52869, Class A2)

Alternator Data	
Manufacturer :	LINZ
Model :	PRO 18SA/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	86.1 %
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Apparent power [kVA]:	23

Available Options	
Diamond offers a range of optional features to tailor our gensets to meet your power requirements.	
Options:	
* A wide range of Sound Attenuated Enclosures	
* A variety of generating set control and synchronising panels	
* Additional alarms and shutdowns	
* A selection of exhaust silencer noise levels	
For further information on all of the standard and optional features for this product, please contact DIAMOND or visit www.diamondcable.com.tr	

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.