DIA- D 300

Output Ratings

Genset Model	Prime[1]	Standby[2]
380-415V, 50Hz	264 kVA / 211 kW	290 kVA / 232 kW
480V, 60Hz	-	-

Ratings are given at 0,8 power factor

Dimension & Weight

Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
3350 / 4260	1550 / 1550	1920 / 2140	2490 / 3370	

Dry: With Lube Oil Wet: With Lube Oil & Coolant

Without canopy/ with canopy

Engine Technical Data

Engine Model :	DEUTZ - BF 6M1015C- LAG1A
Number of Cylinders:	6 / V
Cycle :	4 Stroke
Bore / Stroke [mm] :	132 / 145
Induction :	Turbocharged - İntercooled
Cooling Method :	Water cooled
Governor Type :	Electronic
Compression Ratio :	16.5:1
Displacement [lt] :	11.9
Electrical Sys. Voltage	24 / Negative

Cooling System

	50Hz
Cooling System Capacity [lt] :	100

Lubrication System

Total Oil Capacity [lt] :	38

Exhaust System

	50Hz
Max. Allowable Back Pressure [kPa] :	5
Exhaust Gas Temp. [°C] :	485

Fuel System

Fuel Filter Type :	Replaceable Element
Recommended Fuel :	Class A2 Diesel

Fuel Consumption [lt] :

Prime	110% Load	100% Load	75% Load	50% Load
50Hz	63	55	42	28

Fuel Tank Capacity (L):

(Based on diesel fuel with a spec. gravity of 0,84 and complied with BS2869, Class A2)

Performance

		50Hz
Engine Speed [rpm] :		1500
Gross Engine Power [kW] :		
	Prime	210
	Standby	231

Air Systems

	50Hz
Air Filter Type :	Replaceable Element

Alternator Data

Manufacturer :	Linz Electric
Model :	PRO 28 SD/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	92.7%
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Appearent power [kVA]:	280

Available Options

Diamond offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

* A wide range of Sound Attenuated Enclosures
* A variety of generating set control and synchronising panels
* Additional alarms and shutdowns
* A selection of exhaust silencer noise levels

For further information on all of the standard and optional features for this product, please contact DIAMOND or visit www.diamondcable.com.tr

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25'C Air Inlet Temp. 100m, 30% relative humidity.